

NKE高温浮动预紧碟簧规格表

螺栓规格 BOLT SIZE	尺寸 (MM)				建议载荷 (N) RECOMMEND LOAD	压平载荷 (N) FLAT LOAD	备注
	DE	DI	T	LO			
M10	20.00	10.40	3.00	3.20	14648	18301	
M12	22.00	12.40	3.50	3.72	22469	28074	
M14	25.30	14.40	4.00	4.30	34887	43579	
M16	29.20	16.30	5.00	5.30	50294	62840	
M18	32.50	18.50	5.50	5.80	54158	68659	
M20	40.00	20.40	6.00	6.50	72361	72301	
M22	41.00	22.60	6.50	6.91	75814	94726	
M24	45.00	24.60	7.00	7.50	95252	118992	
M27	52.00	27.60	7.50	8.10	103028	128686	
M30	54.00	30.80	8.00	8.65	133182	166122	
M33	60.00	33.60	9.00	9.70	162576	203073	
M36	65.00	37.00	10.00	10.70	192697	240729	
M39	70.00	40.00	11.00	11.70	221887	277224	
M42	75.00	43.00	12.00	12.80	283537	354233	
M45	80.00	46.00	13.00	13.80	322281	402668	
M48	86.00	49.00	14.00	14.90	388648	485569	
M52	95.00	53.00	15.00	16.00	427476	534061	
M56	104.00	57.00	16.00	17.10	462695	578041	
M64	115.00	65.00	17.00	18.30	558282	697363	
M68	122.00	69.00	17.00	18.30	496326	619972	
M70	125.00	71.00	16.00	17.60	487189	608257	
M72	130.00	73.00	16.00	17.60	446004	556837	
M76	135.00	77.00	17.00	18.60	502783	627812	
M82	145.00	83.00	18.00	19.60	518953	648077	
M85	152.00	86.00	18.00	19.80	525968	656672	
M90	160.00	91.00	18.00	20.00	522389	652020	
M95	165.00	96.00	20.00	22.00	697845	871261	
M100	180.00	102.00	20.00	22.50	716012	893340	

温度范围(TEMPERATURE RANGE) (°C) ≤ 550°C

COATING: GEOMET 500B